Revision 1.1

Supersedes date 04/07/2012



SAFETY DATA SHEET STAINLESS STEEL CLEANER

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name STAINLESS STEEL CLEANER

Internal Id A072

1.2. Relevant identified uses of the substance or mixture and uses advised

<u>against</u>

Identified uses Cleaning agent.

1.3. Details of the supplier of the safety data sheet

ARROW SOLUTIONS Supplier

RAWDON ROAD

MOIRA

SWADLINCOTE DERBYSHIRE DE12 6DA

TEL: +44 (0)1283 221044

EMERGENCY: +44 (0) 777 8505 330

FAX: +44 (0)1283 225731 sales@arrowchem.com

1.4. Emergency telephone number

+44 (0) 777 8505 330

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (1999/45/EEC) F+:R12.

2.2. Label elements

Detergent Labelling:

15 - < 30% Aliphatic hydrocarbons < 5% non-ionic surfactants

1,2-BENZOISOTHIAZOL-3(2H)-ONE Contains

Labelling



Extremely flammable

Risk Phrases

R12 Extremely flammable.

Safety Phrases

Α1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. A2

Do not spray on a naked flame or any incandescent material.

S2 Keep out of the reach of children.

S9 Keep container in a well-ventilated place.

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe vapour/spray.

S35 S51 This material and its container must be disposed of in a safe way. Use only in well-ventilated areas.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

REFINED MINERAL OIL 10-30%

CAS-No.: 8042-47-5 EC No.: 232-455-8 Registration Number: 01-2119487078-27-xxxx

Classification (EC 1272/2008) Classification (67/548/EEC)

Asp. Tox. 1 - H304 Xn;R65.

HYDROCARBON PROPELLANT 10-30%

CAS-No.: 68476-85-7 EC No.: 270-704-2

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12.

ISOPARAFFINIC HYDROCARBON 5-10%

CAS-No.: 90622-57-4 EC No.: 292-459-0 Registration Number: 01-2119471991-29-XXXX

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 3 - H226 Xn;R65. EUH066 R10.R53,R66.

Asp. Tox. 1 - H304 Aquatic Chronic 4 - H413

ALCOHOL ETHOXYLATE SURFACTANT 1-5%

CAS-No.: 24938-91-8 EC No.: 224-540-3

Classification (EC 1272/2008) Classification (67/548/EEC)

Eye Dam. 1 - H318 Xi;R41.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation

Move into fresh air and keep at rest.

Ingestion

Rinse mouth thoroughly. Get medical attention if any discomfort continues.

Skin contact

Wash skin with soap and water. Get medical attention if any discomfort continues.

Eye contact

Rinse the eye with water immediately. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation.

Vapours may cause drowsiness and dizziness.

Ingestion

Due to the physical nature of this material it is unlikely that swallowing will occur.

Skin contact

Prolonged skin contact may cause redness and irritation.

Eye contact

Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment

needed

No specific first aid measures noted.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire

5.3. Advice for firefighters

Special Fire Fighting Procedures

Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency

procedures

Do not smoke, use open fire or other sources of ignition. Do not breathe vapour.

6.2. Environmental precautions

Do not discharge onto the ground or into water courses.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb with inert, damp, non-combustible material, then flush area with water.

6.4. Reference to other sections

For personal protection, see section 8.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Store at moderate temperatures in dry, well ventilated area.

Storage Class

Chemical storage.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
HYDROCARBON PROPELLANT	WEL	600 ppm	1430 mg/m3	750 ppm	1780 mg/m3	
ISOPARAFFINIC HYDROCARBON	WEL		1200 mg/m3			
REFINED MINERAL OIL			5 mg/m3 (Oil mist)			

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment





Engineering measures

No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

Hand protection

For prolonged or repeated skin contact use suitable protective gloves. Use protective gloves made of: Rubber, neoprene or PVC.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Aeroso
Odour Mild.

Solubility Soluble in water.

9.2. Other information

Not determined.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Not determined.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials To Avoid

No incompatible groups noted

10.6. Hazardous decomposition products

Fire or high temperatures create: Carbon dioxide (CO2). Carbon monoxide (CO). Ammonia or amines.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation

Vapours may cause drowsiness and dizziness.

Ingestion

Gastrointestinal symptoms, including upset stomach.

Skin contact

Repeated exposure may cause skin dryness or cracking.

Eye contact

Irritation of eyes and mucous membranes.

Toxicological information on ingredients.

ISOPARAFFINIC HYDROCARBON (CAS: 90622-57-4)
REFINED MINERAL OIL (CAS: 8042-47-5)

Toxicological information

No information available.

Acute toxicity:

Acute Toxicity (Oral LD50)

No information available.

> 5000 mg/kg Rat

Acute Toxicity (Dermal LD50)

No information available.

> 2000 mg/kg Rabbit

Acute Toxicity (Inhalation LC50)

No information available.

> 5200 mg/l (dust/mist) Rat 4 hours

Skin Corrosion/Irritation:

Not irritating.

Respiratory or skin sensitisation:

Respiratory sensitisation

No information available.

Skin sensitisation

No information available.

Carcinogenicity:

Carcinogenicity

No information available.

Reproductive Toxicity:

Reproductive Toxicity - Fertility

No information available.

Reproductive Toxicity - Development

No information available.

Specific target organ toxicity - single exposure:

STOT - Single exposure

No information available.

Specific target organ toxicity - repeated exposure:

STOT - Repeated exposure

No information available.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product is not expected to be toxic to aquatic organisms.

12.1. Toxicity

Ecological information on ingredients.

REFINED MINERAL OIL (CAS: 8042-47-5)

Acute Toxicity - Fish

Not available.

Acute Toxicity - Aquatic Plants

Not available.

Acute Toxicity - Microorganisms

Not available.

12.2. Persistence and degradability

Degradability

The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential

The product is not bioaccumulating.

12.4. Mobility in soil

Mobility:

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. The product is soluble in water.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

<u>14.1. UN number</u>

UN No. (ADR/RID/ADN) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper Shipping Name AEROSOLS

14.3. Transport hazard class(es)

ADR/RID/ADN Class Class 2.1: Flammable gases.

IMDG Class 2.1
ICAO Class/Division 2.1

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group 5F

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No.

14.6. Special precautions for user

Tunnel Restriction Code

(D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC

Code

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for

the substance or mixture

Uk Regulatory References

Chemicals (Hazard Information & Packaging) Regulations.

Statutory Instruments

Control of Substances Hazardous to Health.

Guidance Notes

Workplace Exposure Limits EH40.

EU Legislation

Dangerous Preparations Directive 1999/45/EC.

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

Revision Date 28/08/2012

Revision 1.1

 Supersedes date
 04/07/2012

 Date
 13/11/09

Risk Phrases In Full

R12 Extremely flammable.

R10 Flammable.

R65 Harmful: may cause lung damage if swallowed.

R53 May cause long-term adverse effects in the aquatic environment.

R66 Repeated exposure may cause skin dryness or cracking.

R41 Risk of serious damage to eyes.

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H220 Extremely flammable gas.
 H222 Extremely flammable aerosol.
 H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H318 Causes serious eye damage.

H413 May cause long lasting harmful effects to aquatic life.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.