

Safety Data Sheet

Copyright, 2014, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

3.00 **Document Group:** 28-4553-5 **Version Number:** 07/02/14 07/09/12 **Issue Date: Supercedes Date:**

SECTION 1: Identification

1.1. Product identifier

ScotchgardTM UHS 25 Floor Finish

Product Identification Numbers

70-0715-9148-4, 70-0715-9154-2, 70-0715-9159-1, 70-0716-8337-2, 70-0716-8338-0, 70-0716-8339-8, 70-0716-8339-8, 70-0716-8338-1, 70-0716-838-1, 70-0716-808-1, 70-0716-808-1, 70-0716-808-1, 70-0716-808-1, 70-0716-808-1, 70-0716-808-1, 70-0716-808-1, 70-0716-808-1, 70-0716-808-1, 70-0716-808-1, 70-0716-808-1, 70-0716-8

1.2. Recommended use and restrictions on use

Recommended use

Hard Floor Maintenance

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Commercial Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

2.2. Label elements

Signal word

Warning

Symbols

Not applicable

Pictograms

Not applicable

Hazard Statements

Causes eye irritation.

Precautionary Statements

Prevention:

Wash thoroughly after handling.

ScotchgardTM UHS 25 Floor Finish 07/02/14

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

2.3. Hazards not otherwise classified

None.

19% of the mixture consists of ingredients of unknown acute oral toxicity.

20% of the mixture consists of ingredients of unknown acute dermal toxicity.

27% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
WATER	7732-18-5	60 - 90 Trade Secret *
ACRYLIC COPOLYMER	63744-68-3	10 - 30 Trade Secret *
DIETHYLENE GLYCOL MONOETHYL ETHER	111-90-0	1 - 5 Trade Secret *
TRI(BUTOXYETHYL) PHOSPHATE	78-51-3	1 - 5 Trade Secret *
ACRYLIC COPOLYMER	67892-91-5	0.5 - 1.5 Trade Secret *
ETHOXYLATED ALCOHOLS	84133-50-6	0.5 - 1.5 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide Carbon dioxide

Condition

During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid eye contact. For industrial or professional use only. Avoid breathing fume/vapors. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
DIETHYLENE GLYCOL	111-90-0	AIHA	TWA:140 mg/m3(25 ppm)	
MONOETHYL ETHER				
DIETHYLENE GLYCOL	111-90-0	CMRG	TWA:25 ppm	
MONOETHYL ETHER				

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Page 3 of 9

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control fume/vapors. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Gloves made from the following material(s) are recommended: Butyl Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Full facepiece air-purifying respirator suitable for organic vapors

Half facepiece or full facepiece air-purifying respirator suitable for ammonia/methylamine

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Odor, Color, Grade: Milky white homogeneous emulsion with acrylic odor

Odor threshold No Data Available

8.1 - 9.1

Melting point No Data Available

Boiling Point $> 212 \, {}^{\circ}F$ **Flash Point** No flash point **Evaporation rate** No Data Available Flammability (solid, gas) Not Applicable Flammable Limits(LEL) No Data Available Flammable Limits(UEL) No Data Available No Data Available **Vapor Pressure Vapor Density** No Data Available **Density** No Data Available

Specific Gravity Approximately 1 [Ref Std: WATER=1]

Solubility in Water Complete

Solubility- non-water No Data Available No Data Available **Autoignition temperature Decomposition temperature** No Data Available < 0.5 % weight **Volatile Organic Compounds**

140 - 160 g/l [Test Method: calculated per CARB title 2] **VOC Less H2O & Exempt Solvents**

SECTION 10: Stability and reactivity

Page 4 of 9

ScotchgardTM UHS 25 Floor Finish 07/02/14

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects: **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause target organ effects after inhalation.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause target organ effects after ingestion.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-		No data available; calculated ATE > 50 mg/l
	Vapor(4 hr)		

ScotchgardTM UHS 25 Floor Finish 07/02/14

Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
DIETHYLENE GLYCOL MONOETHYL ETHER	Dermal	Rabbit	LD50 9,143 mg/kg
DIETHYLENE GLYCOL MONOETHYL ETHER	Ingestion	Rat	LD50 5,400 mg/kg
TRI(BUTOXYETHYL) PHOSPHATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
TRI(BUTOXYETHYL) PHOSPHATE	Inhalation-	Rat	LC50 > 6.4 mg/l
	Dust/Mist		
	(4 hours)		
TRI(BUTOXYETHYL) PHOSPHATE	Ingestion	Rat	LD50 4,700 mg/kg
ETHOXYLATED ALCOHOLS	Dermal	Rabbit	LD50 1,127 mg/kg
ETHOXYLATED ALCOHOLS	Inhalation-	Rat	LC50 1.1 mg/l
	Dust/Mist		
	(4 hours)		
ETHOXYLATED ALCOHOLS	Ingestion	Rat	LD50 412 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
DIETHYLENE GLYCOL MONOETHYL ETHER	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
DIETHYLENE GLYCOL MONOETHYL ETHER	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
DIETHYLENE GLYCOL MONOETHYL ETHER	Human	Not sensitizing

Respiratory Sensitization

Germ Cell Mutagenicity

Name	Route	Value
DIETHYLENE GLYCOL MONOETHYL ETHER	In Vitro	Not mutagenic
DIETHYLENE GLYCOL MONOETHYL ETHER	In vivo	Not mutagenic

Carcinogenicity

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
DIETHYLENE GLYCOL MONOETHYL ETHER	Dermal	Not toxic to development	Rat	NOAEL 5,500 mg/kg/day	during organogenesi s
DIETHYLENE GLYCOL MONOETHYL ETHER	Ingestion	Not toxic to development	Mouse	NOAEL 5,500 mg/kg/day	during organogenesi s
DIETHYLENE GLYCOL MONOETHYL ETHER	Inhalation	Not toxic to development	Rat	NOAEL 0.6 mg/l	during organogenesi s
DIETHYLENE GLYCOL MONOETHYL ETHER	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,200 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

specific furger organ rowerty single exposure								
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration		
DIETHYLENE GLYCOL MONOETHYL ETHER	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available			

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
DIETHYLENE GLYCOL MONOETHYL ETHER	Dermal	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 1,000 mg/kg/day	12 weeks
DIETHYLENE GLYCOL MONOETHYL ETHER	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Pig	NOAEL 167 mg/kg/day	90 days
DIETHYLENE GLYCOL MONOETHYL ETHER	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 2,700 mg/kg/day	90 days
DIETHYLENE GLYCOL MONOETHYL ETHER	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	90 days
DIETHYLENE GLYCOL MONOETHYL ETHER	Ingestion	heart hematopoietic system nervous system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 8,100 mg/kg/day	90 days

Aspiration Hazard

<u> </u>	
Name	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations. Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	C.A.S. No	% by Wt
DIETHYLENE GLYCOL MONOETHYL	111-90-0	1 - 5
ETHER (GLYCOL ETHERS)		
TRI(BUTOXYETHYL) PHOSPHATE	78-51-3	1 - 5
(GLYCOL ETHERS)		

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group: 28-4553-5 Version Number: 3.00 07/02/14 **Issue Date: Supercedes Date:** 07/09/12

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR

Page 8 of 9

ScotchgardTM UHS 25 Floor Finish 07/02/14

USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 9 of 9